

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, D.C. 20231
www.uspto.gov

	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
APPLICATION NO.	FILING DATE		222181/00	3010	
09/910,792	07/24/2001	Toshihiro Yoshioka	222101700		
166 7	590 01/07/2003				
466 7 YOUNG & T	370		EXAM	EXAMINER	
745 SOUTH 23	3RD STREET 2ND FLOO	R	DONG, DALEI		
ARLINGTON.	, VA 22202		THE NAME OF THE PARTY OF THE PA		
			ART UNIT	PAPER NUMBER	
			2875		
			DATE MAILED: 01/07/2003		

Please find below and/or attached an Office communication concerning this application or proceeding.

,	Application No.	Applicant(s)	/
	09/910,792	YOSHIOKA ET AL.	11 /
Office Action Summary	Examiner	Art Unit	$-\mathcal{V}$
	Dalei Dong	2875	
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with	the correspondence addre	!SS
A SHORTENED STATUTORY PERIOD FOR REPLY THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If the period for reply specified above is less than thirty (30) days, a reply - If NO period for reply is specified above, the maximum statutory period v - Failure to reply within the set or extended period for reply will, by statute - Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b). Status	within the statutory minimum of thirty (3 and a poly and will expire SIX (6) MONTH cause the application to become ABAN	y be timely filed 30) days will be considered timely. S from the mailing date of this comn DONED (35 U.S.C. § 133).	nunication.
1) Responsive to communication(s) filed on 24 5	<u>uly 2001</u> .		
	is action is non-final.		
3) Since this application is in condition for allowationsed in accordance with the practice under	ance except for formal matte Ex parte Quayle, 1935 C.D.	rs, prosecution as to the 1 11, 453 O.G. 213.	nerits is
Disposition of Claims			
 4) ☐ Claim(s) 1-16 is/are pending in the application 4a) Of the above claim(s) is/are withdraw 			
	WIT HOTH COHOLOGICALICAL		
, —			
6)⊠ Claim(s) <u>1-16</u> is/are rejected. 7)□ Claim(s) is/are objected to.			
8) Claim(s) are subject to restriction and/o	r election requirement.		
Application Papers	, ologion requirements		
9)⊠ The specification is objected to by the Examine	ır.		
10)⊠ The drawing(s) filed on 24 July 2001 is/are: a)[by the Examiner.	
Applicant may not request that any objection to the	e drawing(s) be held in abeyan	ce. See 37 CFR 1.85(a).	
11) ☐ The proposed drawing correction filed on	_ is: a)□ approved b)□ dis	approved by the Examiner	•
If approved, corrected drawings are required in re			
12) The oath or declaration is objected to by the Ex	caminer.		
Priority under 35 U.S.C. §§ 119 and 120			
13) Acknowledgment is made of a claim for foreig	n priority under 35 U.S.C. §	119(a)-(d) or (f).	
a) All b) Some * c) None of:			
1. Certified copies of the priority documen	ts have been received.		
2. Certified copies of the priority documen	ts have been received in Ap	plication No. <u>09/910,792</u>	
 3. Copies of the certified copies of the price application from the International But See the attached detailed Office action for a list 	reau (PCT Rule 17.2(a)).		tage
14) Acknowledgment is made of a claim for domes	tic priority under 35 U.S.C. §	119(e) (to a provisional a	application).
a) The translation of the foreign language pr	ovisional application has be	en received.	
Attachment(s)	•		
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449) Paper No(s)	5) Notice of Ir	ummary (PTO-413) Paper No(s formal Patent Application (PTO) -152)

Art Unit: 2875

DETAILED ACTION

Drawings

1. The drawings are objected to because in Figure 6A, component number 13 points to upper dielectric layer as suppose to lower dielectric layer. A proposed drawing correction or corrected drawings are required in reply to the Office action to avoid abandonment of the application. The objection to the drawings will not be held in abeyance.

Specification

2. The disclosure is objected to because of the following informalities:

On page 15, line 4, "lower dielectric layer 131" should be lower dielectric layer 13.

On page 20, line 11, "Figure 6A and 7B" should be Figure 6A and 6B.

On page 23, line 15, spaces are needed between "electrode121and".

Appropriate correction is required.

Claim Rejections - 35 USC § 102

3. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Art Unit: 2875

Claims 1, 8-10 and 14-16 are rejected under 35 U.S.C. 102(b) as being anticipated by
 U.S. Patent No. 5,210,468 to Yoshioka.

Regarding to claims 1, 8-10 and 14-16, Yoshioka discloses in Figures 3A and 3B, "a glass substrate 1, a pair of aluminum seed discharge electrodes 2 each 0.05 mm wide are formed, defining seed discharge space therebetween, using vacuum evaporation and lithography techniques. An Al₂O₃ layer 3 is formed to 2 µm thick on electrodes. A pair of main discharge electrodes 4 of aluminum each of 0.2 mm wide is formed on the layer 3 to define a main discharge space therebetween and an Al₂O₃ layer 5 is formed on the main discharge electrodes 4 similarly on the layer 3. On the Al₂O₃ layer 5, a MgO layer 6 of 1 μm thick is formed. Then, on the layer 6, a partition wall 7, 0.25 mm high is formed using thick film techniques. Finally, a front glass 10 having a lower surface on which an aluminum write electrode 9 and an Al₂O₃ layer 12 are formed in that order, phosphor 8 is painted on the layer 12 adhered to the partition wall with a gap of 0.3 mm, and the gap is filled with discharge gas 11 of He-Xe (2%) mixture at 80 to 500 torr. Thus, an AC surface discharge type gas discharge display element is formed. In this case, the MgO layer 6 is used to reduce the discharge voltage since MgO has a high efficiency secondary electron emission when by bombarded ion, and the Al₂O₃ layer 5 is used to increase the breakdown voltage of the dielectric" (column 4, line 44-67).

Yoshioka further discloses in Figures 3A and 3B, "applying a 20 KHz AC pulse voltage 2 μ sec wide from a power source 14 to the seed electrode 2 and a 20 KHz AC pulse voltage 0.2 to 5 μ sec wide from a power source 13 to the main discharge electrodes

Page 4

Application/Control Number: 09/910,792

Art Unit: 2875

4" (column 5, line 13-16). As disclosed by Yoshioka, the upper and the lower electrodes can be at equipotential.

Claim Rejections - 35 USC § 103

- 5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 6. Claims 2-7 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent No. 5,210, 468 to Yoshioka.

Regarding to claims 2-7, Yoshioka discloses "instead of the construction shown in Figures 3A and 3B, a construction such as shown in Figures 4A and 4B can be used in which seed electrodes 2 are arranged such that electric field formed thereby is orthogonal to that formed by main discharge electrodes 4" (column 4, line 67-68 to column 5, line 1-4). In Figures 3A and 3B Yoshioka also discloses the upper and lower electrodes are formed symmetrically about the center of a first sustain gap, furthermore, in Figures 4A and 4B Yoshioka discloses the center of the first sustain gap is deviated from a center of second sustain gap. However, Yoshioka does not disclose upper electrodes provided in a plurality of different layers.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to have add additional layers of electrodes within the dielectric layer

Art Unit: 2875

of Yoshioka in order to further enhance the discharge characteristics to obtain a higher discharge efficiency and lower the applied voltage of the discharge display.

7. Claims 11-13 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent No. 5,210, 468 to Yoshioka in view of U.S. Patent No. U.S. Patent No. 5,428,263 to Nagano.

Regarding to claims 11-13, Yoshioka discloses a plasma display panel comprising a substrate having a plurality of electrode pairs covered by a dielectric layer and the upper and lower electrodes being connected at equipotential, moreover, a second substrate arranged in opposing relation and a discharge gas filling gap between the first substrate and the second substrate.

However, Yoshioka does not discloses connecting wiring for electrically connecting upper electrode and the lower electrode. Nagano teaches in Figure 12, a connecting electrodes 13 to connect the cathode pattern 12 and the terminal electrode 3.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to have utilize the connecting electrode of Nagano to connect the upper and lower electrodes of Yoshioka in order to eliminate the problem in withstand voltage and to enhance the trigger effect and superior flexibility and conductivity of the electrodes.

Art Unit: 2875

Conclusion

8. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

The following prior art are cited to further show state of the art of composition of a plasma display panel.

- U.S. Patent No. 5,086,297 to Miyake.
- U.S. Patent No. 5,541,479 to Nagakubo.
- U.S. Patent No. 5,661,500 to Shinoda.
- U.S. Patent No. 5,818,168 to Ushifusa.
- U.S. Patent No. 5,883,462 to Ushifusa.
- U.S. Patent No. 5,952,782 to Nanto.
- U.S. Patent No. 6,084,349 to Ueoka.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Dalei Dong whose telephone number is (703)308-2870. The examiner can normally be reached on 8 A.M. to 5 P.M..

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Sandra O'Shea can be reached on (703)305-4939. The fax phone numbers for the organization where this application or proceeding is assigned are (703)872-9318 for regular communications and (703)872-9319 for After Final communications.

Art Unit: 2875

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is (703)308-0956.

D.D.

December 27, 2002

Sandra O'Shea

Supervisory Patent Examiner

Technology Center 2800